









## huber suhner data sheet coaxial cable enviroflex 400 rev q

Wed, 09 Jan 2019 00:55:00 GMT  
huber suhner data sheet coaxial pdf - HUBER+SUHNER  DATA SHEET Coaxial ...  
Description SUCOFLEX 100, theflexible, high performancemicrowavcabl e  
Technical Data Construction Material Detail Diameter  
Centreconductor Copper, Silver plated Wire Dielectric PTFE ...  
Thu, 27 Dec 2018 04:52:00 GMT  
HUBER+SUHNER DATA SHEET Coaxial Cable: SUCOFLEX 104 Rev.: E - HUBER+SUHNER is certified according to ISO 9001, ISO 14001, AS/EN9100, ISO/TS 16949 and IRIS.  
www.hubersuhner.com  
Waiver: Fact and figures herein are for information only and do not represent any warranty of any kind.  
Thu, 10 Jan 2019 03:45:00 GMT  
Data Sheet - hubersuhner.com - HUBER+SUHNER  DATA SHEET Coaxial Cable Connector: 11\_N-50-12-10/003\_-Rev.: C Document: DOC-0000181659 P Issued: 06.12.10 Uncontrolled Copy Page 1/1 Sun, 06 Jan 2019 14:34:00 GMT  
HUBER+SUHNER DATA SHEET Coaxial Cable Connector: 11 N-50 ... - HUBER+SUHNER  DATA SHEET Coaxial ...  
Electrical Data Impedance 50  $\hat{\text{C}}$  +/- 2 Max. operating frequency 33 GHz Capacitance 92 pF/m Velocityof signalpropagation 71 %

Signaldelay 4.7 ns/m  
Insulation resistance  $\hat{\text{C}}$  1x 10<sup>8</sup> M $\hat{\text{C}}$ m Min. screening effectiveness > 100 dB (up to 4 GHz) Max. operating voltage 1.9 kV rms (at sea level) Test voltage 5 kV rms (50 Hz/1 min) Mechanical Data Weight 5.5 kg/100 m ...  
Wed, 09 Jan 2019 06:17:00 GMT  
HUBER+SUHNER DATA SHEET Coaxial Cable: SUCOFORM 141 CU ... - HUBER+SUHNER  DATA SHEET Coaxial Cable: RG\_179\_B/U Rev.: H Document: DOC-0000177749 Q Issued: 31.03.10 Uncontrolled Copy Page 1/2 Description PTFE - 75 Ohm - single screen Technical Data Construction Material Detail Diameter Centre conductor Steel, Copper+Silver plated Strand-07 0.31 mm Dielectric PTFE 1.55 mm Outer conductor Copper, Silver plated Braid, 94 % 2 mm Jacket FEP RAL 8015 - br 2 ...  
Thu, 03 Jan 2019 20:29:00 GMT  
HUBER+SUHNER DATA SHEET Coaxial Cable: RG 179 B/U Rev.: H - HUBER+SUHNER  DATA SHEET Coaxial Cable: SUCOFLEX\_102 Rev.: G Document: DOC-0000177900 S Issued: 07.09.05 Uncontrolled Copy Page 1/2 Description SUCOFLEX 100, theflexible, high performancemicrowavcabl e  
Technical Data Construction Material Detail Diameter

Centreconductor Copper, Silver plated Wire Dielectric PTFE Outer conductor Copper, Silver plated wrapped Foil, 100 % Outer conductor Copper ...  
Wed, 09 Jan 2019 13:19:00 GMT  
HUBER+SUHNER DATA SHEET Coaxial Cable: SUCOFLEX 102 Rev.: G - HUBER+SUHNER  DATA SHEET Coaxial Cable: RG\_188\_A/U Rev.: K Document: DOC-0000177751 T Issued: 23.06.10 Uncontrolled Copy Page 1/2 Description Fri, 11 Jan 2019 13:31:00 GMT  
HUBER+SUHNER DATA SHEET Coaxial Cable: RG 188 A/U Rev.: K - HUBER+SUHNER  DATA SHEET Coaxial Cable: RG\_214\_/U Rev.: I Document: DOC-0000177761 V Issued: 26.03.09 Uncontrolled Copy Page 1/2 Description PE-50 Ohm - double screen Technical Data Construction Material Detail Diameter Centre conductor Copper, Silver plated Strand-07 2.25 mm Dielectric PE 7.28 mm Outer conductor Copper, Silver plated Braid, 93 % 8 mm Outer conductor Copper, Silver plated ...  
Wed, 09 Jan 2019 05:34:00 GMT  
HUBER+SUHNER DATA SHEET Coaxial Cable: RG 214 /U Rev.: I - HUBER+SUHNER  DATA SHEET Coaxial Cable: RG\_178\_B/U Rev.: G Document: DOC-0000177747 O Issued: 29.08.07

## huber suhner data sheet coaxial cable enviroflex 400 rev q

Uncontrolled Copy Page  
1/2 Description Thu, 29  
Nov 2018 07:41:00 GMT  
HUBER+SUHNER DATA  
SHEET Coaxial Cable: RG  
178 B/U Rev.: G -  
HUBER+SUHNER Â®  
DATA SHEET Coaxial ...  
Electrical Data Impedance  
50 Î© +/- 2 Max. operating  
frequency 33 GHz  
Capacitance 92 pF/m  
Velocityof  
signalpropagation 71 %  
Signaldelay 4.7 ns/m  
Insulation resistance â‰¥  
1x 10<sup>8</sup> MÎ©m Min.  
screening effectiveness >  
100 dB (up to 18 GHz)  
Max. operating voltage 1.9  
kV rms (at sea level) Test  
voltage 5 kV rms (50 Hz/1  
min) Mechanical Data  
Weight 4.7 kg/100 m ...  
HUBER+SUHNER DATA  
SHEET Coaxial Cable:  
SUCOFORM 141 PE Rev.:  
I - HUBER+SUHNER AG  
Datasheets for Coaxial  
Connectors Coaxial  
connectors are composed of  
an insulated central  
conducting wire wrapped in  
another cylindrical  
conductor (the shield). The  
cable is usually wrapped in  
another insulating layer and  
an outer protective layer.  
HUBER+SUHNER AG  
Coaxial Connectors Data  
Sheets ... -

[sitemap indexPopularRandom](#)

[Home](#)